



## Technical specifications

<b>Haigis-constants*</b>	a0 = -0.7633 a1 = 0.1391 a2 = 0.2244
<b>A-constant*</b>	118.895 (SRK/T)
<b>Refractive Index</b>	1.5
<b>Abbe No.</b>	50

\*IOL Con 12.2021

<b>Lens type</b>	One piece capsular bag IOL
<b>Material</b>	Biocompatible hydrophobic acrylic (<0.5%)
<b>Haptic</b>	C Haptic, 0° angulation
<b>Optic</b>	Aspheric optic, 360° cell barrier
<b>Filter</b>	UV filter, blue light filter (optional)
<b>Sterilisation</b>	Ethylene oxide
<b>Injection system</b>	1stInject 2.0HB, 1stInject 2.4HB / Medicel Accuject

## Basis function

Optical Power



Basis V	Art. No. - clear	Art. No. - yellow	Powers	Steps
non-preloaded	B5AD00	B5ADY0	0.0 D to +9.0 D	1.0 D
non-preloaded	B5AD00	B5ADY0	+10.0 D to +30.0 D	0.5 D
preloaded	B5AB00	B5ABY0	0.0 D to +9.0 D	1.0 D
preloaded	B5AB00	B5ABY0	+10.0 D to +30.0 D	0.5 D



For the latest version,  
scan the QR code.  
[1stq.de/basisv1065](https://1stq.de/basisv1065)

**Do you have any  
questions?**  
[info@1stq.de](mailto:info@1stq.de)



1stQ GmbH  
Konrad-Zuse-Ring 23  
68163 Mannheim, Germany  
[www.1stq.de/en](https://www.1stq.de/en)

