Leading
IOL solutions

Basis K

hydrophilic

Single piece, sterile, foldable acrylic spheric hydrophilic posterior chamber intraocular lens (IOL) with UV blocker. The optic is monofocal. The IOL is non-preloaded, which has to be manually loaded into a compatible injector before implantation.



MATERIAL

Copolymer of hydrophobic and hydrophilic monomers with 25% water content and UV blocker	
Refractive Index	1.46
Abbe Number	58

DESIGN

Optic Diameter Overall Diameter	6 mm	12 mm
Optic Design	Spheric - Aberration Neutral Convex-concave (-10.0 D → -1.0 D) Biconvex (0.0 D → +35.0 D)	
Nominal A-constant	118.9	
Haptic Design	C-loops with 9° angulation	
PCO Prevention	360° sharp edge	
Shelf Life	5 years after sterilization	

INJECTION

Estimated Incision Size	2.2 - 2.4 mm
Recommended Injector	Compatibility chart available: 1stq.eu/compatibility/

CONSTANTS
for optical and immersion ultrasound measurements

SRK/T A-Constant	Haigis	Hoffer Q
A = 118.3*	a0 = 0.95 a1 = 0.400 a2 = 0.100	pACD = 5.15

Holladay I	Barrett Universal II	Holladay II
SF = 1.39	LF = 1.52	ACD = 5.14

*Based on IOL Con 03.2023

The safety and performance of 1stQ IOLs have been tested in clinical investigations and the clinical data demonstrate that these IOLs meet the requirements of the state of the art.

MA-IOL-HPS6C-MD112-DTS-EN 202608
Rev: 1074-V02-03/2026

Basis K

hydrophilic

POWER RANGE

Article No. Clear	SEQ/Powers	Steps	Cylinders	Steps	Addition
611HPS	0.0 D to +9.0 D	1.0 D	-	-	-
611HPS	+10.0 D to +30.0 D	0.5 D	-	-	-

1stQ GmbH
Konrad-Zuse-Ring 23 | 68163 Mannheim
Germany

Leading
IOL solutions

www.1stq.eu
www.1stq.de/en